

ECO-LITE

PRODUCTS

33 Rockland Park Ave, Tappan, NY 10983
 Tel. 800-345-9652 Fax 845-365-9777
www.eco-lite.com

Factor	Specifications
Dimensions (mm)	PAR 38
Base	E 26
Input (V)	AC 110 - 130
Power Consumption (W)	9/12/18/24/27/36 Watts
Power Factor	>=0.9
Efficiency (%)	80
Luminous Flux (Lumen)	486/648/675/900/1000/1250 @ Minardi Custom Color Temperature
Luminaire Efficacy (Lm/W)	>60
Color Temperature	Custom Color by
	Minardi Color Perfect Lighting™
CRI	>80
Beam Angle	15-60°
Dimming	Both dimmable and non-dimmable
Water Resistance	IP60
Heat Sink	Heat Sink : ΔT 32 °C
Lifetime (Hours)	> 50,000
Operating Temperature	-20 ~ 40 (°C)



MINARDI LIGHTING

"For Professionals By Professionals"

Task Light: Par 38 LED

This Minardi Color Perfect Lighting™ fixture allows you to see all the details of your haircuts and hair coloring . It gives off no heat and you only need one per chair. It is extremely energy efficient and is rated for 50,000 hrs.

DISTANCE TO PLANE	INITIAL FOOTCANDLES	BEAM DIAMETER
2'	270	18"
3'	112	30"
4'	68	36"
5'	45	48"
6'	30	60"
7'	21	72"
8'	16	84"
9'	11	96"
10'	9	108"